

Einfach
besser!

MicroCAFS PBK®
patented mixing technology

MC6SP10

Tragbare Geräte für Profis

| | |
|------------------|--|
| Durchfluss: | 11 l/min. (nass) 5.4 l/min. (trocken) |
| Einsatzzeit: | 55 sek. (nass) 115 sek. (trocken) |
| Reichweite: | 11.5 m (nass) 8 m (trocken) |
| Behältergröße: | 10.4 l |
| Arbeitsdruck: | ca. 8 bar |
| Treibgas: | 2 l / 300 bar Druckluft |
| Temperatur: | 0°C - 60°C |
| Gewicht: | 12.5 kg leer, 22.5 kg gefüllt |
| Abmessungen: | 625 x 300 x 220 mm (HxBxT) |
| Löschmittel: | zugelassene Schaummittel |
| Rating EN3: | bis zu 43 A 233 B (löschmittelabhängig) |
| elektr. Anlagen: | Sicherheitsabstände beachten |

Stand 05/2015, Änderungen vorbehalten

Ihr Händler:



www.microcafs.de

MicroCAFS PBK GmbH ■ Burgwaldring 4 ■ 86697 Oberhausen

Simply
better!

MicroCAFS[®] PBK[®]
patented mixing technology

MC6SP10

Portable for professionals

| | |
|----------------------|---|
| Flow rate: | 11 l/min. (wet) 5.4 l/min. (dry) |
| Operating time: | 55 sec. (wet) 115 sec. (dry) |
| Work range: | 11.5 m (wet) 8 m (dry) |
| Vessel capacity: | 10.4 l |
| Operating pressure: | approx. 8 bar |
| Propellant: | 2 l / 300 bar compressed air |
| Temperature: | 0°C - 60°C |
| Weight: | 12.5 kg empty, 22.5 kg filled |
| Size: | 625 x 300 x 220 mm (HxWxD) |
| Extinguishing agent: | approved foam agent |
| Rating EN3: | up to 43 A 233 B (depending of foam agent) |
| Electric area: | consider safety distance |

Status 05-2015, subject to modifications

Your distributor:



www.microcafs.com

MicroCAFS PBK GmbH ■ Burgwaldring 4 ■ 86697 Oberhausen ■ Germany